


F42SF224MOTE940NW

**FIL45 G2 SUR 2240 4480 9NW TECH WH****Description:**

LAMP suspended or surface mounted structure FIL45 G2 SUR 2240. Manufactured from extruded aluminum with an 80% recycling rate, optic and black mat polycarbonate reflector TECH ULTRACONFORT to control light distribution and reduce glare UGR <15. Model for LED MID-POWER, colour temperature 4000K and IRC90. Electronic ON OFF gear included. IP20, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED life time: 90.000 L80 B10. Available finishes: White, black and grey. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** Matte white RAL 9010**Dimensions:** 2.238 x 45 x 80 mm**Weight:** 4.970 g**Installation:** Surface**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	3.657 lm	<b>°K :</b>	4000
<b>Plum:</b>	29,7W	<b>CRI :</b>	90
<b>Efficacy:</b>	123,1 lm/w	<b>R9 :</b>	67
<b>UGR:</b>	<15	<b>MacAdam:</b>	3
<b>Type:</b>	MID POWER	<b>Power Supply:</b>	220-240V 50/60Hz
<b>LED Lifetime:</b>	90.000 L80 B10 (Ta=25°C)	<b>Gear:</b>	Electronic
<b>Power:</b>	26W		

**Light output tolerance +/- 10%****CUSTOM MADE OPTIONS:**

PHOTOMETRIC DATA :

