


F42SF224MOTE940NW



FIL45 G2 SUR 2240 4480 9NW TECH WH

Description:

LAMP suspended or surface mounted structure FIL45 G2 SUR 2240. Manufactured from extruded aluminum with an 80% recycling rate, optic and black mat polycarbonate reflector TECH ULTRACONFORT to control light distribution and reduce glare UGR <15. Model for LED MID-POWER, colour temperature 4000K and IRC90. Electronic ON OFF gear included. IP20, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED life time: 90.000 L80 B10. Available finishes: White, black and grey. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finition: Blanc mat RAL 9010

Dimensions: 2.238 x 45 x 80 mm

Poids: 4.970 g

Installation: Surface

SPÉCIFICATIONS TECHNIQUES:

Flux lumineux:	3.657 lm	°K :	4000
Plum:	29,7W	IRC :	90
Efficacité:	123,1 lm/w	R9 :	67
UGR:	<15	MacAdam:	3
Type:	MID POWER	Alimentation:	220-240V 50/60Hz
Durée de vie LED:	90.000 L80 B10 (Ta=25°C)	Équipement:	Électronique
Puissance:	26W		

Tolérance de flux lumineux +/- 10%

**OPTIONS PERSONNALISABLES:**

DONNÉES PHOTOMÉTRIQUES :

