


F52RC170HOPR840NG



FIL 50 G2 PRISM REC 9200 NW GR.

Description:

Structure to recessed model FIL 50 REC 1700 LAMP brand. Made in extruded recycled aluminum with a rate of 80%, with prismatic diffuser en polycarbonate translucide et un film optique pour un contrôle de la distribution lumineuse procurant un facteur d'éblouissement inférieur à UGR19. Model for LED MID-POWER, colour temperature 4000K with CRI80 and with electronic wiring included. With IP42, IK07 protection rating. Insulation Class I. Photobiological safety group 0. LED lifetime: 70.000 L80 B10. Available finishes: White and grey. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Gloss grey

Dimensions: 1.700 x 66 x 67 mm

Weight: 2.860 g


Installation: Recessed

Recessing measures: 1,710 x 52 x 80 mm

TECHNICAL SPECIFICATIONS:

Light output:	5.913 lm	°K :	4000
Plum:	55W	CRI :	80
Efficacy:	107,5 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	MID POWER LED	Gear:	Electronic
LED Lifetime:	70.000 L80 B10 (Ta=25°C)		
Power:	55W		


Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



PHOTOMETRIC DATA :




ACCESORIES :

Assembly



Product code:
ELWRST

Description:
ACC. ELECTROSTATICS WRIST STRAP




Product code:
F5COX/MMG
F5COX/MMW
F5PRREX/MMG
F5PRREX/MMW

Description:
FIL 50 ACC. COVER X/MM GR.
FIL 50 ACC. COVER X/MM WH.
FIL 50 ACC. REC PROFIL X/MM GR.
FIL 50 ACC. REC PROFIL X/MM WH.




Product code:
F5JO

Description:
ACC. INTM JOINT B



Product code:
F5REECG
F5REECW

Description:
FIL 50 ACC. REC END COVER GR.
FIL 50 ACC. REC END COVER WH.



Product code:
F5REHCG
F5REHCW

Description:
FIL 50 ACC. REC 90° CORNER GR.
FIL 50 ACC. REC 90° CORNER WH.