


## F53RE112MOPR830DG




## - FIL50 G3 REC 1120 2600 WW PRISM DALI GR

**Description:**


LAMP recessed structure FIL 50 REC 1120. Manufactured from extruded aluminum with an 80% recycling rate, diffuser made of prismatic polycarbonate to control light distribution and reduce glare UGR<19. Model for LED MID-POWER, colour temperature 3000K with CRI80 and DALI electronic gear included. IP43, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED lifetime: 72.000 L80 B10. White and grey finishes available. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** Gloss grey**Dimensions:** 1.123 x 66 x 67 mm**Weight:** 2.166 g**Installation:** Recessed**Recessing measures:** 1,133 x 52 x 80 mm**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	2.315 lm	<b>°K :</b>	3000
<b>Plum:</b>	21,50W	<b>CRI :</b>	80
<b>Efficacy:</b>	107,7 lm/w	<b>MacAdam:</b>	3
<b>UGR:</b>	<19	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Type:</b>	MID POWER LED	<b>Gear:</b>	Adjustable DALI
<b>LED Lifetime:</b>	72.000 L80 B10 (Ta=25°C)		
<b>Power:</b>	17.9W		

**Light output tolerance +/- 10%****CUSTOM MADE OPTIONS:**

PHOTOMETRIC DATA :



ACCESORIES :

Assembly




**Product code:**

ELWRST

**Description:**

ACC. ELECTROSTATICS WRIST STRAP



**Product code:**

F5COX/MMG

F5COX/MMW

F5PRREX/MMG

F5PRREX/MMW

**Description:**

FIL 50 ACC. COVER X/MM GR.

FIL 50 ACC. COVER X/MM WH.

FIL 50 ACC. REC PROFIL X/MM GR.

FIL 50 ACC. REC PROFIL X/MM WH.




**Product code:**

F5JO

**Description:**

ACC. INTM JOINT B



**Product code:**


F5REECG

F5REECW

**Description:**

FIL 50 ACC. REC END COVER GR.

FIL 50 ACC. REC END COVER WH.



**Product code:**

F5REHCG

F5REHCW

**Description:**

FIL 50 ACC. REC 90° CORNER GR.

FIL 50 ACC. REC 90° CORNER WH.