Product datasheet

FIL 70 TECH

F71RE100LOTS840DG




FIL 70 TECH REC 1M 1600 NW DALI GR.

Description:

Recessed luminaire model FIL 70 TECH REC 1M 1600 NW DALI GR., LAMP brand. Made of satin grey painted extruded aluminium. Model for MID-POWER LED with neutral white colour temperature and control DALI gear included, Glare rating <19 (for 4h, 8h 70/50/20). which consists of a two-phase reflection. Insulation class I. Photobiological safety group 0. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Gloss grey

Dimensions: 1.000 x 70 x 70 mm Weight: 2.124 g



Installation: Recessed

1,012 x 78 x 85 mm Recessing measures:

TECHNICAL SPECIFICATIONS:

Light output: 1.530 lm °K: 4000 Plum: 14,5W CRI: 80 Efficacy: 105,5 lm/w 3 MacAdam:

UGR: <19

Type: MID POWER LED Gear: Adjustable DALI

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

12W Power:

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:



















Power Supply:

220-240V 50/60Hz





FIL 70 TECH




F71RE100LOTS840DG


FIL 70 TECH REC 1M 1600 NW DALI GR.

PHOTOMETRIC DATA:

4740123 η = 100% lmax = 716 cd/klmUTE: 1,00A

CIE: 85 100 100 100 100





| alpha = 81,0° | H (m) | D (m) | Emax | Emed |
|---------------|-------|-------|------|------|
| | 1 | 1,71 | 931 | 558 |
| | 2 | 3,42 | 233 | 140 |
| | 3 | 5,13 | 103 | 62 |
| | 4 | 6,84 | 58 | 35 |

FIL 70 TECH



ACCESORIES:

Assembly



Product code:

ELWRST



ACC. ELECTROSTATICS WRIST STRAP



Product code:

F7J0

Description:

ACC. INTM JOINT



Product code:

F7REECG F7REECW

Description:

FIL 70 ACC. REC END COVER GR. FIL 70 ACC. REC END COVER WH.



Product code:

F7TEREHCG F7TEREHCW

Description:

FIL 70 TECH ACC. REC 90° CORNER GR.
FIL 70 TECH ACC. REC 90° CORNER WH.

ACCESORIES:

Optical



Product code:

Description:

DIOPST1000 ACC. DIF. SOFT TECH OPAL

Data according to regulations 2019/2020/EU and 2019/2015/EU