Product datasheet

FIL 70

F71RE120LOOP830NW



FIL 70 OPAL REC 2600 WW WH.

Description:

Recessed luminaire model FIL 70 OPAL REC 2600 WW WH., LAMP brand. Made of matt white painted extruded aluminium with opal polycarbonate diffuser. Model for LED MID-POWER with warm white colour temperature and control gear included. IP43, IK06 protectio n rating. Insulation class I. Photobiological safety group 0. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010 Dimensions:

1.162 x 89 x 70 mm Weight: 2.662 g

Installation: Recessed

1,174 x 78 x 85 mm Recessing measures:

TECHNICAL SPECIFICATIONS:

Light output: 1.992 lm °K: 3000 Plum: 19,2W CRI: 80 Efficacy: 103,8 lm/w 3 MacAdam:

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L80 B10 (Ta=25°C) Gear: Electronic

17W Power:

Light output tolerance +/- 10%



CLASE



























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU
















FIL 70









PHOTOMETRIC DATA:







Product datasheet

FIL 70



ACCESORIES:

Assembly



Product code:

ELWRST



ACC. ELECTROSTATICS WRIST STRAP



Product code:

F7J0



ACC. INTM JOINT



Product code:

F7REECW

Description:

FIL 70 ACC. REC END COVER WH.



Product code:

F7REHCW

Description:

FIL 70 ACC. REC 90° CORNER WH.

ACCESORIES:

Optical



Product code:

Description:

F7DIX/MMOP FIL 70 ACC. OPAL DIFFUSER X/MM

Data according to regulations 2019/2020/EU and 2019/2015/EU

FIL 70



