
F71RE170HOPR830NW



FIL 70 PRISM REC 6600 WW WH.

Description:

Recessed luminaire model FIL 70 PRISM REC 6600 WW WH., LAMP brand. Made of matt white painted extruded aluminium with prismatic polycarbonate diffuser. Model for MID-POWER LED, with warm white colour temperature and control gear included. Glare rating <19 (for 4h, 8h 70/50/20). IP43, IK06 protection rating. Insulation class I. Photobiological safety group 0. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010 1.743 x 70 x 70 mm Dimensions:

Weight: 4.426 g

Installation: Recessed

1,755 x 78 x 85 mm Recessing measures:

TECHNICAL SPECIFICATIONS:

Light output: 5.260 lm °K: 3000 Plum: 42,8W CRI: 80 Efficacy: 122,9 lm/w 3 MacAdam:

UGR: <19 Power Supply: 220-240V 50/60Hz

Type: MID POWER LED Gear: Electronic

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

41W Power:

Light output tolerance +/- 10%



CLASE



























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU
























PHOTOMETRIC DATA:

14741730 $_{\eta}$ = 100% I_{η} = 625 cd/klm UTE: 1,00B I_{η} CIE: 70 96 99 100 100







H (m)	D (m)	Emax	Emed
1	1,62	3265	1682
2	3,23	816	421
3	4,85	363	187
4	6,46	204	105



ACCESORIES:

Assembly



Product code:

ELWRST

Description:

ACC. ELECTROSTATICS WRIST STRAP



Product code:

F7COSUX/MMG F7COSUX/MMW

Description:

FIL 70 ACC. COVER X/MM GR. FIL 70 ACC. COVER X/MM WH.



Product code:

F7JO

Description:

ACC. INTM JOINT



Product code:

F7PRREX/MMG F7PRREX/MMW

Description:

FIL 70 ACC. REC PROFILE X/MM GR. FIL 70 ACC. REC PROFILE X/MM WH.



Product code:

F7REECG F7REECW

Description:

FIL 70 ACC. REC END COVER GR. FIL 70 ACC. REC END COVER WH.



Product code:

F7TEREHCG F7TEREHCW

Description:

FIL 70 TECH ACC. REC 90° CORNER GR. FIL 70 TECH ACC. REC 90° CORNER WH.



