#### F71RE170HOPR840NG



#### FIL 70 PRISM REC 6600 NW GR.

#### Description:

Recessed luminaire model FIL 70 PRISM REC 6600 NW GR., LAMP brand. Made of satin grey painted extruded aluminium with prismatic polycarbonate diffuser. Model for MID-POWER LED, with neutral white colour temperature and control gear included. Glare rati ng <19 (for 4h, 8h 70/50/20). IP43, IK06 protection rating. Insulation class I. Photobiological safety group 0. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Gloss grey

Dimensions: 1.743 x 70 x 70 mm Weight: 4.426 g

Installation: Recessed

1,755 x 78 x 85 mm Recessing measures:

#### **TECHNICAL SPECIFICATIONS:**

Light output: 5.452 lm °K: 4000 Plum: 42,8W CRI: 80 Efficacy: 127,4 lm/w 3 MacAdam:

UGR: <19

Type: MID POWER LED

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

41W Power:

### Light output tolerance +/- 10%



CLASE















Power Supply:

Gear:













# **CUSTOM MADE OPTIONS:**























220-240V 50/60Hz

Electronic


Data according to regulations 2019/2020/EU and 2019/2015/EU





# F71RE170HOPR840NG

# FIL 70 PRISM REC 6600 NW GR.

### **PHOTOMETRIC DATA:**







H (m)	D (m)	Emax	Emed
1	1,62	3384	1744
2	3,23	846	436
3	4,85	376	194
4	6,46	212	109



# ACCESORIES:

# **Assembly**



Product code:

ELWRST

#### Description:

ACC. ELECTROSTATICS WRIST STRAP



Product code:

F7COSUX/MMG F7COSUX/MMW

#### Description:

FIL 70 ACC. COVER X/MM GR. FIL 70 ACC. COVER X/MM WH.



Product code:

F7JO

# Description:

ACC. INTM JOINT



Product code:

F7PRREX/MMG F7PRREX/MMW

#### Description:

FIL 70 ACC. REC PROFILE X/MM GR. FIL 70 ACC. REC PROFILE X/MM WH.



Product code:

F7REECG F7REECW

# Description:

FIL 70 ACC. REC END COVER GR. FIL 70 ACC. REC END COVER WH.



# Product code:

F7TEREHCG F7TEREHCW

### Description:

FIL 70 TECH ACC. REC 90° CORNER GR. FIL 70 TECH ACC. REC 90° CORNER WH.



