F71RE170HOPR840NW



FIL 70 PRISM REC 6600 NW WH.

Description:

Recessed luminaire model FIL 70 PRISM REC 6600 NW WH., LAMP brand. Made of matt white painted extruded aluminium with prismatic polycarbonate diffuser. Model for MID-POWER LED, with neutral white colour temperature and control gear included. Glare rati ng <19 (for 4h, 8h 70/50/20). IP43, IK06 protection rating. Insulation class I. Photobiological safety group 0. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010

1.743 x 70 x 70 mm Dimensions: Weight: 4.426 g

Installation: Recessed

1,755 x 78 x 85 mm Recessing measures:

TECHNICAL SPECIFICATIONS:

Light output: 5.452 lm °K: 4000 Plum: 42,8W CRI: 80 Efficacy: 127,4 lm/w 3 MacAdam:

UGR: <19 Power Supply: 220-240V 50/60Hz

Type: MID POWER LED Gear: Electronic

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

41W Power:

Light output tolerance +/- 10%



CLASE



























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU






















FIL 70 PRISM REC 6600 NW WH.



PHOTOMETRIC DATA:







H (m)	D (m)	Emax	Emed
1	1,62	3384	1744
2	3,23	846	436
3	4,85	376	194
4	6,46	212	109



ACCESORIES:

Assembly



Product code:

ELWRST

Description:

ACC. ELECTROSTATICS WRIST STRAP



Product code:

F7COSUX/MMG F7COSUX/MMW

Description:

FIL 70 ACC. COVER X/MM GR. FIL 70 ACC. COVER X/MM WH.



Product code:

F7JO

Description:

ACC. INTM JOINT



Product code:

F7PRREX/MMG F7PRREX/MMW

Description:

FIL 70 ACC. REC PROFILE X/MM GR. FIL 70 ACC. REC PROFILE X/MM WH.



Product code:

F7REECG F7REECW

Description:

FIL 70 ACC. REC END COVER GR. FIL 70 ACC. REC END COVER WH.



Product code:

F7TEREHCG F7TEREHCW

Description:

FIL 70 TECH ACC. REC 90° CORNER GR. FIL 70 TECH ACC. REC 90° CORNER WH.



