Product datasheet

FINE CURVE

FC1500LO68OP8300W



FINECURVE IP67 24V 2600LM 50W 830 5MX19

Description:

Flexible strip model FINECURVE IP67 24V 2600LM 50W 830 5MX19 LAMP brand. Model for MID-POWER LED, warm white color temperature. IP67 protection rating. Insulation class III. Supplied with a 5 meters.

Matte white RAL 9010 Finish:

Weight: 1.000 g



Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 2.275 lm °K: 3000

> CRI: 80

Type: MID POWER EPISTAR MacAdam: 3

LED Lifetime: 36.000 Power Supply: 24V 50-60Hz

Power: 55W Gear: Without gear (requires external gear)

Light output tolerance +/- 10%















+34937366800

FINE CURVE





FINECURVE IP67 24V 2600LM 50W 830 5MX19




PHOTOMETRIC DATA:

FC1500LO68OP8300W η = 101% Imax = 336 cd/klm UTE: 1,00E + 0,01T CIE: 45 76 94 99 101







Product datasheet

FINE CURVE



ACCESORIES:

Assembly



Product code:

CT4P67N ACC. IP67 4P CONNECTOR

Description:



Product code:

FC1FX30G

Description:

FINE CURVE LED ACC.WALL BRACKET 25MM GR

ACCESORIES:

Adjustment and control



Product code:

Description:

DRV2010024D DRV 100W 24V 220-240V DA IND.



Product code: DRV6710024N Description:

DRV 100W 24V 100-305V NR IP67



Product code:

Description:

DRV688024N ACC. DRIVER IP68 24V 80W