Product datasheet

FINE CURVE

FC2100LO67OP9400W

FINECURVE IP67 24V 500LM 10W 940 1M

Description:

Flexible strip model FINECURVE 1M LAMP brand. Model for MID POWER LED, 4000K color temperature, CRI 90. IP67 protection rating. Insulation class III. Lifetime: 36.000. Supplied with a 1 meter.

Finish: Matte white RAL 9010

Weight: 1.000 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	450 lm	**ºK :**	4000
		CRI :	90
Type:	MID POWER LED	**MacAdam:**	3
LED Lifetime:	36.000 (Ta=25ºC)	**Power Supply:**	24V 50-60Hz
Power:	10W	**Gear:**	Without gear (requires external gear)

Light output tolerance +/- 10%

FINE CURVE

FC2100LO67OP9400W **FINECURVE IP67 24V 500LM 10W 940 1M**

PHOTOMETRIC DATA :

FC2100LO67OP9400W

η = 102%

Imax = 332 cd/klm

UTE: 0,98E + 0,04T

CIE: 46 77 95 96 102









LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Data according to regulations 2019/2020/EU and 2019/2015/EU

ACCESORIES :

Assembly

Product code:	Description:
CT4P67N	ACC. IP67 4P CONNECTOR

Product code:	Description:
FC1FX30G	FINE CURVE LED ACC.WALL BRACKET 25MM GR

ACCESORIES :

Adjustment and control

Product code:	Description:
DRV2010024D	DRV 100W 24V 220-240V DA IND.

Product code:	Description:
DRV202024N	ACC. DRIVER 24V 20W

Product code:	Description:
DRV6710024N	DRV 100W 24V 100-305V NR IP67

Product code:	Description:
DRV688024N	ACC. DRIVER IP68 24V 80W

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Data according to regulations 2019/2020/EU and 2019/2015/EU