Product datasheet

FINE CURVE

FC2500LO67OP9300W



FINECURVE IP67 24V 2500LM 50W 930 5M

Description:

Flexible strip model FINECURVE 5M LAMP brand. Model for MID POWER LED, 3000K color temperature, CRI 90. IP67 protection rating. Insulation class III. Lifetime: 36.000. Supplied with a 5 meters.



Matte white RAL 9010 Finish:

Weight: 1.000 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 2.100 lm °K: 3000

> CRI: 90

Type: MID POWER LED MacAdam: 3

LED Lifetime: 36.000 (Ta=25°C) Power Supply: 24V 50-60Hz

Power: 50W Gear: Without gear (requires external gear)

Light output tolerance +/- 10%















Data according to regulations 2019/2020/EU and 2019/2015/EU

+34937366800

FINE CURVE





FC2500LO67OP9300W


FINECURVE IP67 24V 2500LM 50W 930 5M

PHOTOMETRIC DATA:

FC2500LO67OP9300W η = 102% lmax = 332 cd/klmUTE: 0,98E + 0,04T CIE: 46 77 95 96 102







Product datasheet

FINE CURVE



ACCESORIES:

Assembly



Product code:

CT4P67N

Description:

ACC. IP67 4P CONNECTOR



Product code:

FC1FX30G

Description:

FINE CURVE LED ACC.WALL BRACKET 25MM GR

ACCESORIES:

Adjustment and control



Product code:

Description:

DRV2010024D DRV 100W 24V 220-240V DA IND.



Product code:

DRV6710024N

Description:

DRV 100W 24V 100-305V NR IP67



Product code:

Description:

DRV688024N ACC. DRIVER IP68 24V 80W