#### **Product datasheet**

#### **GAP**


# **GA215WF840NI**



# **GAP G2 1400 NW WFL INOX**

# Description:

Outdoor recessed Downlight/Uplight model GAP G2 1400, LAMP brand. Made of injected aluminium, with a cataphoresis treatment, lacquered in black colour, tempered glass and exterior ring made of stainless steel AISI 316. Model with HI-POWER LED, with 4000K colour temperature, CRI 80 and control gear included. With Wide Flood optics. It allows for a rotation from 0° to 90°, and a tilt between -30° and 30°. With a grades of protection IP67, IK10. Insulation class I. Lifetime: 60.000 L90 B10



ø270 mm

Finish: Stainless steel AISI 316

Weight: 3.800 g

Installation: Floor recessed

# **TECHNICAL SPECIFICATIONS:**

Light output: 1.092 lm °K: 4000 Plum: 11,9W CRI: 80 Efficacy: 91,8 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

10W Power:

#### Light output tolerance +/- 10%





















































# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU


















#### **GA215WF840NI GAP G2 1400 NW WFL INOX**





# **PHOTOMETRIC DATA:**

GA215WF840NI  $\eta$  = 100% Imax = 1438 cd/klm UTE: 1,00A

CIE: 89 98 100 100 100







# **Product datasheet**

# **GAP**



# ACCESORIES:

# **Assembly**



Product code: GAREBOB

Description:

GAP ACC. REC BOX



GARERIRDM

Description:

GAP ACC. REC CEILING RING

# **GAP**



