Product datasheet

GAP


GA235MF840NI



GAP G2 3600 NW MFL INOX

Description:

Outdoor recessed Downlight/Uplight model GAP G2 3600, LAMP brand. Made of injected aluminium, with a cataphoresis treatment, lacquered in black colour, tempered glass and exterior ring made of stainless steel AISI 316. Model with HI-POWER LED, with 4000K colour temperature, CRI 80 and control gear included. With Medium Flood optics. It allows for a rotation from 0° to 90°, and a tilt between -30° and 30°. With a grades of protection IP67, IK10. Insulation class I. Lifetime: 60.000 L90 B10



ø270 mm

Finish: Stainless steel AISI 316

Weight: 3.800 g

Installation: Floor recessed

TECHNICAL SPECIFICATIONS:

Light output: 2.851 lm °K: 4000 Plum: 33,5W CRI: 80 Efficacy: 85,1 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

30W Power:

Light output tolerance +/- 10%

































CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















GAP

GA235MF840NI GAP G2 3600 NW MFL INOX




PHOTOMETRIC DATA:

GA235MF840NI η = 100% Imax = 4976 cd/klm

UTE: 1,00A

CIE: 89 98 100 100 100



Product datasheet

GAP



ACCESORIES:

Assembly



Product code: GAREBOB

Description:

GAP ACC. REC BOX



GARERIRDM

Description:

GAP ACC. REC CEILING RING

GAP



