HANCE DOWNLIGHT

LAMP Worktitude for light


HD1SR30MF830NBW



HANCE DOWN SEMIREC 3000 WW MFL WH.

Description:

Multidirectional semi-recessed downlight, model HANCE DOWN SEMIREC 3000 WW MFL WH., LAMP brand. Body and frame made of injected aluminium in textured white colour and decorative rings made of injected polycarbonate in white colour. Passive dissipation for a proper thermal management. Model with LED COB, with a warm white colour temperature and control gear included. With Meidum Flood high purity aluminium reflector. It allows for a rotation of 355° and a tilt up to 85°. Insulation class II.



Finish: Texturised white RAL 9010

Weight: 1.540 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 2.816 lm
 °K:
 3000

 Plum:
 28,2W
 CRI:
 80

 Efficacy:
 99,8 lm/w
 MacAdam:
 3

Type: COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 25W

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















HANCE DOWNLIGHT




HD1SR30MF830NBW

HANCE DOWN SEMIREC 3000 WW MFL WH.

PHOTOMETRIC DATA:

HD1SR30MF830NBW $_{\eta}$ = 100% $_{lmax}$ = 4409 cd/klm UTE: CIE: 102 100 100 100 100



| alpha = 24,2° | H (m) | D (m) | Emax | Emed |
|---------------|-------|-------|-------|------|
| \wedge | 1 | 0,43 | 12382 | 8853 |
| | 2 | 0,86 | 3096 | 2213 |
| | 3 | 1,29 | 1376 | 984 |
| | 4 | 1,72 | 774 | 553 |

Tel. +34937366800 Web www.lamp.es

HANCE DOWNLIGHT



ACCESORIES:

Optical



Product code:

HSCU75



HANCE 3000/4000 ACC. CUTTING BEAM



Product code:

HSHO75



HANCE 3000/4000 ACC. HONEYCOMB GRILLE



Product code:

HSRI90B



HANCE 3000/4000 ACC. RING DECO BK.



Product code:

HSRI90C



HANCE 3000/4000 ACC. RING DECO CO.



Product code:

HSRI90M

Description:

HANCE 3000/4000 ACC. RING DECO MET.



Product code:

HSRI90W

Description:

HANCE 3000/4000 ACC. RING DECO WH.



Product code:

Description:

HSTR75 HANCE 3000/4000 ACC. DIF TRANS