HANCE DOWNLIGHT

Worktitude for light


HD1SR40SP830NBW



HANCE DOWN SEMIREC 4000 WW SP WH.

Description:

Multidirectional semi-recessed downlight, model HANCE DOWN SEMIREC 4000 WW SP WH., LAMP brand. Body and frame made of injected aluminium in textured white colour and decorative rings made of injected polycarbonate in white colour. Passive dissipation for a proper thermal management. Model with LED COB, with a warm white colour temperature and control gear included. With Spot high purity aluminium reflector. It allows for a rotation of 355° and a tilt up to 85°. Insulation class II.



Finish: Texturised white RAL 9010

Weight: 1.540 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 3.518 lm
 °K:
 3000

 Plum:
 37,6W
 CRI:
 80

 Efficacy:
 93,6 lm/w
 MacAdam:
 3

Type: COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 34W

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















HANCE DOWNLIGHT




HD1SR40SP830NBW

HANCE DOWN SEMIREC 4000 WW SP WH.

PHOTOMETRIC DATA:

HD1SR40SP830NBW η = 100% Imax = 6494 cd/klm UTE: CIE: 103 100 100 100 100



alpha = 17,6°	H (m)	D (m)	Emax	Emed
\wedge	1	0,31	22736	16161
	2	0,62	5684	4040
	3	0,93	2526	1796
	4	1,24	1421	1010

HANCE DOWNLIGHT



ACCESORIES :

Optical



Product code:

HSCU75



HANCE 3000/4000 ACC. CUTTING BEAM



Product code:

HSEL75



HANCE 3000/4000 ACC. ELIPTICAL LENS



Product code:

HSHO75

Description:

HANCE 3000/4000 ACC. HONEYCOMB GRILLE



Product code:

HSRI90B

Description:

HANCE 3000/4000 ACC. RING DECO BK.



Product code:

HSRI90C

Description:

HANCE 3000/4000 ACC. RING DECO CO.



Product code:

HSRI90M

Description:

HANCE 3000/4000 ACC. RING DECO MET.



Product code:

HSRI90W

Description:

HANCE 3000/4000 ACC. RING DECO WH.



Product code:

HSTR75

Description:

HANCE 3000/4000 ACC. DIF TRANS

Data according to regulations 2019/2020/EU and 2019/2015/EU