HANCE DOWNLIGHT



HD2RE10FL840NW



HANCE G2 DOWN REC 1000 NW FL WH

Description:

LAMP multidirectional recessed downlight HANCE G2 DOWN REC 1000. Allowing 355° rotation and tilting up to 30°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 35º flood reflector. LED COB, 4000K and CRI80. Electronic ON OFF control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 78.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 1.071 lm °K: 4000 Plum: 8,6W CRI: 80 Efficacy: 124,5 lm/w R9: 66 UGR: <19 MacAdam: 3

Type: COB Power Supply: 220-240V 50/60Hz

LED Lifetime: 78.000 L80B10 (Ta=25°C) Gear: Electronic

7W Power:

Light output tolerance +/- 10%





























CUSTOM MADE OPTIONS:





Data according to regulations 2019/2020/EU and 2019/2015/EU

















HANCE DOWNLIGHT





HD2RE10FL840NW


HANCE G2 DOWN REC 1000 NW FL WH

PHOTOMETRIC DATA:

HD2RE10FL840NW η = 100% Imax = 2218 cd/klm UTE: CIE: 100 100 100 100 100







HANCE DOWNLIGHT



ACCESORIES:

Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50



HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65B

Description:

HANCE 1000/2000 ACC. RING DECO BK.



Product code:

HSRI65C

Description:

HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS