HANCE DOWNLIGHT



HD2RE20FL840DB



HANCE G2 DOWN REC 2000 NW FL DALI BK

Description:

LAMP multidirectional recessed downlight HANCE G2 DOWN REC 2000. Allowing 355° rotation and tilting up to 30°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 35° flood reflector. LED COB, 4000K and CRI80. Electronic DALI control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 2.371 lm °K: 4000 Plum: 20,8W CRI: 80 Efficacy: 114 lm/w R9: 66 Type: СОВ MacAdam: 3

 LED Lifetime:
 72.000 L80B10 (Ta=25°C)
 Power Supply:
 220-240V 50/60Hz

 Power:
 18W
 Gear:
 Adjustable DALI

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU















HANCE DOWNLIGHT





HD2RE20FL840DB


HANCE G2 DOWN REC 2000 NW FL DALI BK

PHOTOMETRIC DATA:

HD2RE20FL840DB η = 100% Imax = 2218 cd/klm UTE: CIE: 100 100 100 100 100







HANCE DOWNLIGHT



ACCESORIES:

Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50



HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65B

Description:

HANCE 1000/2000 ACC. RING DECO BK.



Product code:

HSRI65C

Description:

HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS