HANCE DOWNLIGHT



HD2RE20MF830NW



HANCE G2 DOWN REC 2000 WW MFL WH

Description:

LAMP multidirectional recessed downlight HANCE G2 DOWN REC 2000. Allowing 355° rotation and tilting up to 30°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25º middle flood reflector. LED COB, 3000K and CRI80. Electronic ON OFF control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 2.267 lm °K: 3000 Plum: 20,8W CRI: 80 Efficacy: 109 lm/w R9: 60 UGR: <19 MacAdam: 3

Type: COB Power Supply: 220-240V 50/60Hz

LED Lifetime: 72.000 L80B10 (Ta=25°C) Gear: Electronic

18W Power:

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:























HANCE DOWNLIGHT





HD2RE20MF830NW


HANCE G2 DOWN REC 2000 WW MFL WH

PHOTOMETRIC DATA:

HD2RE20MF830NW
η = 100%
Imax = 3354 cd/klm
UTE:
CIE: 101 100 100 100 100







Data according to regulations 2019/2020/EU and 2019/2015/EU

HANCE DOWNLIGHT



ACCESORIES:

Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50



HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65B

Description:

HANCE 1000/2000 ACC. RING DECO BK.



Product code:

HSRI65C

Description:

HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS