

HANCE DOWNLIGHT

HD2RE30MF840DB




HANCE G2 DOWN REC 3000 NW MFL DALI BK

Description:

LAMP multidirectional recessed downlight HANCE G2 DOWN REC 3000. Allowing 355° rotation and tilting up to 30°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25° middle flood reflector. LED COB, 4000K and CRI80. Electronic DALI control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 78.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.

Finish: Texturised black RAL 9011

Installation: Recessed

**TECHNICAL SPECIFICATIONS:**

Light output:	3.549 lm	°K :	4000
Plum:	28,3W	CRI :	80
Efficacy:	125,4 lm/w	R9 :	64
UGR:	<19	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	78.000 L80B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	25W		


Light output tolerance +/- 10%

**CUSTOM MADE OPTIONS:**

HD2RE30MF840DB

HANCE G2 DOWN REC 3000 NW MFL DALI BK

PHOTOMETRIC DATA :



ACCESSORIES :

Optical



Product code:
HS2HO75

Description:
HANCE G2 3000/4000 ACC. HONEYCOMB GRILLE



Product code:
HS2RI90C

Description:
HANCE G2 3000/4000 ACC. RING DECO CO.




Product code:
HS2RI90M

Description:
HANCE G2 3000/4000 ACC. RING DECO MET.



Product code:
HS2RI90W

Description:
HANCE G2 3000/4000 ACC. RING DECO WH.



Product code:
HS2TR75

Description:
HANCE G2 3000/4000 ACC. DIF TRANS