### HANCE DOWNLIGHT



### HD2RE40FL840DW



### HANCE G2 DOWN REC 4000 NW FL DALI WH

### Description:

LAMP multidirectional recessed downlight HANCE G2 DOWN REC 4000. Allowing 355° rotation and tilting up to 30°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 35º flood reflector. LED COB, 4000K and CRI80. Electronic DALI control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

Installation: Recessed

### **TECHNICAL SPECIFICATIONS:**

Light output: 4.467 lm °K: 4000 Plum: 36,7W CRI: 80 Efficacy: 121,7 lm/w R9: 64 Type: СОВ MacAdam: 3

LED Lifetime: 72.000 L80B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz 33W Gear: Power: Adjustable DALI

## Light output tolerance +/- 10%























### **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU















# **HANCE DOWNLIGHT**



HD2RE40FL840DW

### HANCE G2 DOWN REC 4000 NW FL DALI WH

### **PHOTOMETRIC DATA:**

HD2RE40FL840DW  $\eta$  = 100% lmax = 2005 cd/klmUTE: CIE: 100 100 100 100 100





