HANCE DOWNLIGHT



HD2RE40FL840NB



HANCE G2 DOWN REC 4000 NW FL BK

Description:

LAMP multidirectional recessed downlight HANCE G2 DOWN REC 4000. Allowing 355° rotation and tilting up to 30°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 35° flood reflector. LED COB, 4000K and CRI80. Electronic ON OFF control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.





Finish: Texturised black RAL 9011

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 4.467 lm °K: 4000 Plum: 36,7W CRI: 80 Efficacy: 121,7 lm/w R9: 64 Type: СОВ MacAdam: 3

LED Lifetime: 72.000 L80B10 (Ta=25°C) **Power Supply:** 220-240V 50/60Hz

Power: 33W Gear: Electronic

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU















HANCE DOWNLIGHT



HD2RE40FL840NB

HANCE G2 DOWN REC 4000 NW FL BK

PHOTOMETRIC DATA:







