#### **Product datasheet**

# HANCE DOWNLIGHT

## HD2RE40MF840NB



### HANCE G2 DOWN REC 4000 NW MFL BK

#### **Description:**

Finish:

LAMP multidirectional recessed downlight HANCE G2 DOWN REC 4000. Allowing 355° rotation and tilting up to 30°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25° middle flood reflector. LED COB, 4000K and CRI80. Electronic ON OFF control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.

155 0-30°

Texturised black RAL 9011

Installation: Recessed

#### **TECHNICAL SPECIFICATIONS:**

Light output:	4.591 lm	°K :	4000
Plum:	36,7W	CRI :	80
Efficacy:	125,1 lm/w	R9 :	64
UGR:	<19	MacAdam:	3
Туре:	СОВ	Power Supply:	220-240V 50/60Hz
LED Lifetime:	72.000 L80B10 (Ta=25°C)	Gear:	Electronic
Power:	33W		

#### Light output tolerance +/- 10%



## CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light

## Product datasheet

# HANCE DOWNLIGHT

## HD2RE40MF840NB

HANCE G2 DOWN REC 4000 NW MFL BK



## **PHOTOMETRIC DATA :**

