HANCE DOWNLIGHT




HD2RE40MF940DW



HANCE G2 DOWN REC 4000 9NW MFL DALI WH

Description:

LAMP multidirectional recessed downlight HANCE G2 DOWN REC 4000. Allowing 355° rotation and tilting up to 30°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25º middle flood reflector. LED COB, 4000K and CRI90. Electronic DALI control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.907 Im °K: 4000 Plum: 36,7W CRI: 90 Efficacy: 106,5 lm/w R9: 64 UGR: <19 MacAdam: 3

Type: COB Power Supply: 220-240V 50/60Hz LED Lifetime: 72.000 L80B10 (Ta=25°C) Gear: Adjustable DALI

33W Power:

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















HANCE DOWNLIGHT



HD2RE40MF940DW

HANCE G2 DOWN REC 4000 9NW MFL DALI WH

PHOTOMETRIC DATA:

HD2RE40MF940DW η = 100% Imax = 3926 cd/klm UTE:

CIE: 101 100 100 100 100

