

HANCE DOWNLIGHT

HD2RE40MF940NW



HANCE G2 DOWN REC 4000 9NW MFL WH

Description:

LAMP multidirectional recessed downlight HANCE G2 DOWN REC 4000. Allowing 355° rotation and tilting up to 30°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25° middle flood reflector. LED COB, 4000K and CRI90. Electronic ON OFF control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.

Finish: Texturised white RAL 9010

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	3.907 lm	°K :	4000
Plum:	36,7W	CRI :	90
Efficacy:	106,5 lm/w	R9 :	64
UGR:	<19	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	72.000 L80B10 (Ta=25°C)	Gear:	Electronic
Power:	33W		

Light output tolerance +/- 10%

**CUSTOM MADE OPTIONS:**

HD2RE40MF940NW

HANCE G2 DOWN REC 4000 9NW MFL WH

PHOTOMETRIC DATA :

