## HANCE DOWNLIGHT

# LAMP Worktitude for light


## HD2RE40SP840NW



## HANCE G2 DOWN REC 4000 NW SP WH

## Description:

LAMP multidirectional recessed downlight HANCE G2 DOWN REC 4000. Allowing 355° rotation and tilting up to 30°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 4000K and CRI80. Electronic ON OFF control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

Installation: Recessed

## **TECHNICAL SPECIFICATIONS:**

Light output: 4.694 lm °K: 4000 Plum: 36,7W CRI: 80 Efficacy: 127,9 lm/w R9: 64 UGR: <19 MacAdam: 3

Type: COB Power Supply: 220-240V 50/60Hz

LED Lifetime: 72.000 L80B10 (Ta=25°C) Gear: Electronic

Power: 33W

# Light output tolerance +/- 10%























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU


















# HANCE DOWNLIGHT





HD2RE40SP840NW


# HANCE G2 DOWN REC 4000 NW SP WH

# **PHOTOMETRIC DATA:**









Data according to regulations 2019/2020/EU and 2019/2015/EU