

HD2SR07SS930DB



HANCE G2 DOWN SEMIREC 700 9WW SSP DA BK

Description:

LAMP multidirectional semi-recessed downlight HANCE G2 DOWN SEMIREC 700. Allowing 355° rotation and tilting up to 85°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 10° super spot polycarbonate optics. LED HIGH POWER, 3000K and CRI90. Electronic DALI control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 60.000 L90B10 (Ta=25°C). Available finishes: Textured white and textured black.

Finish: Texturised black RAL 9011

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	438 lm	°K :	3000
Plum:	8,6W	CRI :	90
Efficacy:	51 lm/w	R9 :	53
UGR:	<16	MacAdam:	3
Type:	HIGH POWER	Power Supply:	220-240V 50/60Hz
LED Lifetime:	60.000 L90B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	7W		

Light output tolerance +/- 10%

**CUSTOM MADE OPTIONS:**

HD2SR07SS930DB

HANCE G2 DOWN SEMIREC 700 9WW SSP DA BK

PHOTOMETRIC DATA :

