## **HANCE DOWNLIGHT**



#### HD2SR10FL940DB




#### HANCE G2 DOWN SEMIREC 1000 9NW FL DA BK

#### Description:

LAMP multidirectional semi-recessed downlight HANCE G2 DOWN SEMIREC 1000. Allowing 355° rotation and tilting up to 85°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 35° flood reflector. LED COB, 4000K and CRI90. Electronic DALI control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 78.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.

Finish: Texturised black RAL 9011



## Installation: Recessed

#### **TECHNICAL SPECIFICATIONS:**

Light output: 914 lm °K: 4000 Plum: 8,6W CRI: 90 Efficacy: 106,3 lm/w R9: 66 UGR: <19 MacAdam: 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 78.000 L80B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 7W

### Light output tolerance +/- 10%























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU

















#### HANCE DOWNLIGHT




HD2SR10FL940DB


## HANCE G2 DOWN SEMIREC 1000 9NW FL DA BK


### **PHOTOMETRIC DATA:**


HD2SR10FL940DB  $\eta$  = 100% Imax = 2218 cd/klm UTE:


CIE: 100 100 100 100 100




















Data according to regulations 2019/2020/EU and 2019/2015/EU

## **HANCE DOWNLIGHT**



# ACCESORIES:

## Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50

Description:

HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65B

#### Description:

HANCE 1000/2000 ACC. RING DECO BK.



Product code:

HSRI65C

Description:

HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

## Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS