HANCE DOWNLIGHT




HD2SR40FL830NW



HANCE G2 DOWN SEMIREC 4000 WW FL WH

Description:

LAMP multidirectional semi-recessed downlight HANCE G2 DOWN SEMIREC 4000. Allowing 355° rotation and tilting up to 85°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 35º flood reflector. LED COB, 3000K and CRI80. Electronic ON OFF control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 4.225 lm °K: 3000 Plum: 36,7W CRI: 80 Efficacy: 115,1 lm/w R9: 61 Type: СОВ MacAdam: 3

LED Lifetime: 72.000 L80B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz

33W Gear: Power: Electronic

Light output tolerance +/- 10%





























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU
















HANCE DOWNLIGHT





HD2SR40FL830NW


HANCE G2 DOWN SEMIREC 4000 WW FL WH

PHOTOMETRIC DATA:









HANCE DOWNLIGHT



ACCESORIES:

Optical



Product code:

HS2HO75



Product code:

HANCE G2 3000/4000 ACC. HONEYCOMB GRILLE HS2RI90C



HANCE G2 3000/4000 ACC. RING DECO CO.



Product code:

HS2RI90M



HANCE G2 3000/4000 ACC. RING DECO MET.

Product code:

HS2RI90W

Description:

HANCE G2 3000/4000 ACC. RING DECO WH.



Product code:

Description:

Description:

HS2TR75 HANCE G2 3000/4000 ACC. DIF TRANS