HANCE DOWNLIGHT

LAMPWorktitude for light


HD2SR40FL940DB



HANCE G2 DOWN SEMIREC 4000 9NW FL DA BK

Description:

LAMP multidirectional semi-recessed downlight HANCE G2 DOWN SEMIREC 4000. Allowing 355° rotation and tilting up to 85°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 35° flood reflector. LED COB, 4000K and CRI90. Electronic DALI control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.800 lm °K: 4000 Plum: 36,7W CRI: 90 Efficacy: 103,5 lm/w R9: 64 Type: СОВ MacAdam: 3

 LED Lifetime:
 72.000 L80B10 (Ta=25°C)
 Power Supply:
 220-240V 50/60Hz

 Power:
 33W
 Gear:
 Adjustable DALI

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU















HANCE DOWNLIGHT



HD2SR40FL940DB

HANCE G2 DOWN SEMIREC 4000 9NW FL DA BK

PHOTOMETRIC DATA:

HD2SR40FL940DB η = 100% lmax = 2005 cd/klmUTE: CIE: 100 100 100 100 100

