

HANCE DOWNLIGHT

HD2SR40MF840NB



HANCE G2 DOWN SEMIREC 4000 NW MFL BK

Description:

LAMP multidirectional semi-recessed downlight HANCE G2 DOWN SEMIREC 4000. Allowing 355° rotation and tilting up to 85°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25° middle flood reflector. LED COB, 4000K and CRI80. Electronic ON OFF control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.

Finish: Texturised black RAL 9011

Installation: Recessed

TECHNICAL SPECIFICATIONS:

| | | | |
|----------------------|-------------------------|----------------------|------------------|
| Light output: | 4.591 lm | °K : | 4000 |
| Plum: | 36,7W | CRI : | 80 |
| Efficacy: | 125,1 lm/w | R9 : | 64 |
| UGR: | <19 | MacAdam: | 3 |
| Type: | COB | Power Supply: | 220-240V 50/60Hz |
| LED Lifetime: | 72.000 L80B10 (Ta=25°C) | Gear: | Electronic |
| Power: | 33W | | |

Light output tolerance +/- 10%

**CUSTOM MADE OPTIONS:**

HD2SR40MF840NB

HANCE G2 DOWN SEMIREC 4000 NW MFL BK

PHOTOMETRIC DATA :

