Product datasheet

HERMETICA

Worktitude for light


HM10684565OP840NW



HERMETICA 686X667 4500 IP65 NW OPAL WH.

Description:

Recessed luminaire model HERMETICA 686X667 4500 IP65 NW OPAL WH,. LAMP brand. Made of white-lacquered steel plate. Outer frame made of extruded aluminium. Model for lamp LED MID-POWER, with neutral white color temperature and built-in electronic equipment control gear included. With opal polycarbonate diffuser. IP65, IK09 protection rating. Insulation class I. Can be opened for maintenance from below.



Weight: 10.856 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 4.075 lm
 °K:
 4000

 Plum:
 34,1W
 CRI:
 80

 Efficacy:
 119,5 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 30.8W

Light output tolerance +/- 10%





















Data according to regulations 2019/2020/EU and 2019/2015/EU













HERMETICA







PHOTOMETRIC DATA:


HM10684565OP840NW


 $\eta = 100\%$

lmax = 391 cd/klm

UTE: 1,00E

CIE: 50 82 98 100 100





alpha = 104,4°	H (m)	D (m)	Emax	Emed
	1	2,58	1589	546
	2	5,16	397	136
	3	7,74	177	61
	4	10,32	99	34