Worktitude for light

HS2SF10MF830DB



HANCE G2 SUR 1000 WW MFL DALI BK

Description:

LAMP surface multidirectional spotlight HANCE G2 SUR 1000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25° middle flood reflector. LED COB, 3000K and CRI80. Electronic DALI control gear included.IP20, IK07 ratings.Insulation Class I. LED life time: 78.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.022 lm °K: 3000 Plum: 8,6W CRI: 80 Efficacy: 118,8 lm/w R9: 60 UGR: <19 MacAdam: 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 78.000 L80B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 7W

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:


























HANCE G2 SUR 1000 WW MFL DALI BK

PHOTOMETRIC DATA:

 $\begin{array}{l} \mbox{HS2SF10MF830DB} \\ \eta = 100\% \\ \mbox{Imax} = 3354 \mbox{ cd/klm} \\ \mbox{UTE:} \\ \mbox{CIE:} \ 101 \ 100 \ 100 \ 100 \ 100 \end{array}$







Data according to regulations 2019/2020/EU and 2019/2015/EU



ACCESORIES:

Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50



HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65C

Description:

HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

HSSL50

Description:

HANCE 1000/2000 ACC. SOFT LENS



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS