HS2SF10SP840DW



HANCE G2 SUR 1000 NW SP DALI WH

Description:

LAMP surface multidirectional spotlight HANCE G2 SUR 1000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 4000K and CRI80. Electronic DALI control gear included IP20, IK07 ratings. Insulation Class I. LED life time: 78.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.054 lm °K: 4000 Plum: 8,6W CRI: 80 Efficacy: 122,6 lm/w R9: 66 UGR: <16 MacAdam: 3

Type: COB Power Supply: 220-240V 50/60Hz LED Lifetime: 78.000 L80B10 (Ta=25°C) Gear: Adjustable DALI

7W Power:

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















HS2SF10SP840DW


HANCE G2 SUR 1000 NW SP DALI WH

PHOTOMETRIC DATA:

HS2SF10SP840DW η = 100% Imax = 4956 cd/klm UTE: CIE: 102 100 100 100 100









ACCESORIES:

Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50



HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65C

Description:

HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

HSSL50

Description:

HANCE 1000/2000 ACC. SOFT LENS



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS