Worktitude for light

HS2SF20FL940DW




HANCE G2 SUR 2000 9NW FL DALI WH

Description:

LAMP surface multidirectional spotlight HANCE G2 SUR 2000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 35° flood reflector. LED COB, 4000K and CRI90. Electronic DALI control gear included.IP20, IK07 ratings. Insulation Class I. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.

Finish: Texturised white RAL 9010



Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 2.022 lm °K: 4000 Plum: 20,8W CRI: 90 Efficacy: 97,2 lm/w R9: 66 Type: СОВ MacAdam: 3

 LED Lifetime:
 72.000 L80B10 (Ta=25°C)
 Power Supply:
 220-240V 50/60Hz

 Power:
 18W
 Gear:
 Adjustable DALI

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU


















PHOTOMETRIC DATA:


$$\label{eq:eta} \begin{split} &\text{HS2SF20FL940DW} \\ &\eta = 100\% \\ &\text{Imax} = 2218 \text{ cd/klm} \\ &\text{UTE:} \end{split}$$


CIE: 100 100 100 100 100






















ACCESORIES:

Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50



HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65C

Description:

HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

HSSL50

Description:

HANCE 1000/2000 ACC. SOFT LENS



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS