Worktitude for light

HS2SF20MF940DB



HANCE G2 SUR 2000 9NW MFL DALI BK

Description:

LAMP surface multidirectional spotlight HANCE G2 SUR 2000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25° middle flood reflector. LED COB, 4000K and CRI90. Electronic DALI control gear included.IP20, IK07 ratings.Insulation Class I. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 2.049 Im °K: 4000 Plum: 20,8W CRI: 90 Efficacy: 98,5 lm/w R9: 66 UGR: <19 MacAdam: 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 72.000 L80B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 18W

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:
























PHOTOMETRIC DATA:


HS2SF20MF940DB η = 100% Imax = 3354 cd/klm UTE:


CIE: 101 100 100 100 100






















ACCESORIES:

Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50



HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65C

Description:

HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

HSSL50

Description:

HANCE 1000/2000 ACC. SOFT LENS



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS