# Worktitude for light

# HS2SF20SP830DB



#### HANCE G2 SUR 2000 WW SP DALI BK

#### Description:

LAMP surface multidirectional spotlight HANCE G2 SUR 2000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 3000K and CRI80. Electronic DALI control gear included.IP20, IK07 ratings. Insulation Class I. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Surface

#### **TECHNICAL SPECIFICATIONS:**

Light output: 2.204 lm °K: 3000 Plum: 20,8W CRI: 80 Efficacy: 106 lm/w R9: 60 UGR: <19 MacAdam: 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 72.000 L80B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 18W

#### Light output tolerance +/- 10%























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU
















# HANCE G2 SUR 2000 WW SP DALI BK

#### **PHOTOMETRIC DATA:**

HS2SF20SP830DB  $\eta$  = 100% Imax = 4956 cd/klm UTE: CIE: 102 100 100 100 100









# ACCESORIES:

# Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50



HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65C

#### Description:

HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

# Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

# Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

HSSL50

# Description:

HANCE 1000/2000 ACC. SOFT LENS



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS