


## HS2SF30FL840NB




### HANCE G2 SUR 3000 NW FL BK

### Description:

LAMP surface multidirectional spotlight HANCE G2 SUR 3000 . Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 35° flood reflector. LED COB, 4000K y CRI80. Electronic ON OFF control gear included.IP20, IK07 ratings. Insulation Class I. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.





Installation: Surface

### **TECHNICAL SPECIFICATIONS:**

Light output: 3.318 lm °K: 4000 Plum: 28,3W CRI: 80 Efficacy: 117,2 lm/w R9: 64 UGR: <19 MacAdam: 3

Type: COB Power Supply: 220-240V 50/60Hz

LED Lifetime: 72.000 L80B10 (Ta=25°C) Gear: Electronic

Power: 25W

### Light output tolerance +/- 10%





















# **CUSTOM MADE OPTIONS:**



























## HS2SF30FL840NB


## HANCE G2 SUR 3000 NW FL BK

## PHOTOMETRIC DATA:

HS2SF30FL840NB  $\eta$  = 100% Imax = 2005 cd/klm UTE: CIE: 100 100 100 100 100









ACCESORIES:

Optical



Product code: Description:

HSSL50 HANCE 1000/2000 ACC. SOFT LENS