


HS2SF30MF840DB




HANCE G2 SUR 3000 NW MFL DALI BK

Description:

LAMP surface multidirectional spotlight HANCE G2 SUR 3000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25° middle flood reflector. LED COB, 4000K and CRI80. Electronic DALI control gear included.IP20, IK07 ratings.Insulation Class I. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.





Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 3.549 lm °K: 4000 Plum: 28,3W CRI: 80 Efficacy: 125,4 lm/w R9: 64 UGR: <19 MacAdam: 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 72.000 L80B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 25W

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU



















HS2SF30MF840DB


HANCE G2 SUR 3000 NW MFL DALI BK

PHOTOMETRIC DATA:

HS2SF30MF840DB η = 100% Imax = 3926 cd/klm UTE: CIE: 101 100 100 100 100









ACCESORIES:

Optical



Product code: Description:

HSSL50 HANCE 1000/2000 ACC. SOFT LENS