


## HS2SF30SP830DB



### HANCE G2 SUR 3000 WW SP DALI BK

### Description:

LAMP surface multidirectional spotlight HANCE G2 SUR3000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 3000K and CRI80. Electronic DALI control gear included IP20, IK07 ratings. Insulation Class I. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Surface

### **TECHNICAL SPECIFICATIONS:**

Light output: 3.233 Im °K: 3000 Plum: 28,3W CRI: 80 Efficacy: 114,2 lm/w R9: 61 UGR: <19 MacAdam: 3

Type: COB Power Supply: 220-240V 50/60Hz LED Lifetime: 72.000 L80B10 (Ta=25°C) Gear: Adjustable DALI

25W Power:

## Light output tolerance +/- 10%

























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU

















## HS2SF30SP830DB


## HANCE G2 SUR 3000 WW SP DALI BK

### **PHOTOMETRIC DATA:**

HS2SF30SP830DB  $\eta$  = 100% Imax = 5192 cd/klm UTE: CIE: 102 100 100 100 100









ACCESORIES:

Optical



Product code:

Description:

HSSL50

HANCE 1000/2000 ACC. SOFT LENS