Worktitude for light

HS2SF30SP930NB



HANCE G2 SUR 3000 9WW SP BK

Description:

LAMP surface multidirectional spotlight HANCE G2 SUR3000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 3000K y CRI90. Electronic ON OFF control gear included.IP20, IK07 ratings. Insulation Class I. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 2.759 lm °K: 3000 Plum: 28,3W CRI: 90 Efficacy: 97,5 lm/w R9: 61 UGR: <19 MacAdam: 3

Type: COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 72.000 L80B10 (Ta=25°C) Gear: Electronic

Power: 25W

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU


















PHOTOMETRIC DATA:


HS2SF30SP930NB η = 100% Imax = 5192 cd/klm UTE:


CIE: 102 100 100 100 100






















ACCESORIES:

Optical



Product code:

Description:

HSSL50

HANCE 1000/2000 ACC. SOFT LENS