

HS2SF40FL940NW



HANCE G2 SUR 4000 9NW FL WH

Description:

LAMP surface multidirectional spotlight HANCE G2 SUR 4000 . Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 35° flood reflector. LED COB, 4000K y CRI90. Electronic ON OFF control gear included.IP20, IK07 ratings. Insulation Class I. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 3.800 lm °K: 4000 Plum: 36,7W CRI: 90 Efficacy: 103,5 lm/w R9: 64 Type: СОВ MacAdam: 3

LED Lifetime: 72.000 L80B10 (Ta=25°C) **Power Supply:** 220-240V 50/60Hz

Power: 33W Gear: Electronic

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:
























PHOTOMETRIC DATA:


$$\label{eq:eta} \begin{split} &\text{HS2SF40FL940NW} \\ &\eta = 100\% \\ &\text{Imax} = 2005 \text{ cd/kIm} \\ &\text{UTE:} \end{split}$$


CIE: 100 100 100 100 100



















ACCESORIES:

Optical



Product code:

Description:

HSSL50

HANCE 1000/2000 ACC. SOFT LENS