


# HS2SF40MF830NB



# HANCE G2 SUR 4000 WW MFL BK

# Description:

LAMP surface multidirectional spotlight HANCE G2 SUR 4000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25° middle flood reflector. LED COB, 3000K y CRI80. Electronic ON OFF control gear included.IP20, IK07 ratings.Insulation Class I. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Surface

# **TECHNICAL SPECIFICATIONS:**

Light output: 4.343 lm °K: 3000 Plum: 36,7W CRI: 80 Efficacy: 118,3 lm/w R9: 61 UGR: <19 MacAdam: 3

**Type:** COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 72.000 L80B10 (Ta=25°C) Gear: Electronic

Power: 33W

# Light output tolerance +/- 10%





















# **CUSTOM MADE OPTIONS:**

























# HS2SF40MF830NB


# HANCE G2 SUR 4000 WW MFL BK

# **PHOTOMETRIC DATA:**

HS2SF40MF830NB  $\eta$  = 100% Imax = 3926 cd/klm UTE: CIE: 101 100 100 100 100









ACCESORIES:

Optical



Product code:

Description:

HSSL50

HANCE 1000/2000 ACC. SOFT LENS