Worktitude for light


HS2SF40MF840DB



HANCE G2 SUR 4000 NW MFL DALI BK

Description:

LAMP surface multidirectional spotlight HANCE G2 SUR 4000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25° middle flood reflector. LED COB, 4000K and CRI80. Electronic DALI control gear included.IP20, IK07 ratings.Insulation Class I. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 4.591 lm °K: 4000 Plum: 36,7W CRI: 80 Efficacy: 125,1 lm/w R9: 64 UGR: <19 MacAdam: 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 72.000 L80B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 33W

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:

























HS2SF40MF840DB


HANCE G2 SUR 4000 NW MFL DALI BK

PHOTOMETRIC DATA:

HS2SF40MF840DB η = 100% Imax = 3926 cd/klm UTE: CIE: 101 100 100 100 100









ACCESORIES:

Optical



Product code:

Description:

HSSL50

HANCE 1000/2000 ACC. SOFT LENS