HS2SF40SP840DW

HANCE G2 SUR 4000 NW SP DALI WH

Description:

LAMP surface multidirectional spotlight HANCE G2 SUR 4000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 4000K and CRI80. Electronic DALI control gear included IP20, IK07 ratings. Insulation Class I. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 4.694 lm °K: 4000 Plum: 36,7W CRI: 80 Efficacy: 127,9 lm/w R9: 64 UGR: <19 MacAdam: 3

Type: COB Power Supply: 220-240V 50/60Hz LED Lifetime: 72.000 L80B10 (Ta=25°C) Gear: Adjustable DALI

33W Power:

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:

























PHOTOMETRIC DATA:

HS2SF40SP840DW η = 100% Imax = 5192 cd/klm UTE:











ACCESORIES:

Optical



Product code:

Description:

HSSL50

HANCE 1000/2000 ACC. SOFT LENS