# Worktitude for light

#### HS2SF40SP930DW

#### HANCE G2 SUR 4000 9WW SP DALI WH

#### Description:

LAMP surface multidirectional spotlight HANCE G2 SUR 4000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 3000K and CRI90. Electronic DALI control gear included.IP20, IK07 ratings. Insulation Class I. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

Installation: Surface

#### **TECHNICAL SPECIFICATIONS:**

Light output: 3.789 lm °K: 3000 Plum: 36,7W CRI: 90 Efficacy: 103,2 lm/w R9: 61 UGR: <19 MacAdam: 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 72.000 L80B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 33W

### Light output tolerance +/- 10%





















## CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU
















### **PHOTOMETRIC DATA:**


$$\label{eq:eta} \begin{split} &\text{HS2SF40SP930DW} \\ &\eta = 100\% \\ &\text{Imax} = 5192 \text{ cd/kIm} \\ &\text{UTE:} \end{split}$$


CIE: 102 100 100 100 100






















ACCESORIES:

Optical



Product code:

Description:

HSSL50

HANCE 1000/2000 ACC. SOFT LENS