


## HS2SR10MF830DB



## HANCE G2 SEMIREC 1000 WW MFL DALI BK

## Description:

LAMP semi-recessed multidirectional spotlight HANCE G2 SEMIREC 1000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25° middle flood reflector. LED COB, 3000K and CRI80. Electronic DALI control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 78.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Semi-Recessed

## **TECHNICAL SPECIFICATIONS:**

Light output: 1.022 lm °K: 3000 Plum: 8,6W CRI: 80 Efficacy: 118,8 lm/w R9: 60 UGR: <19 MacAdam: 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 78.000 L80B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 7W

## Light output tolerance +/- 10%





















## **CUSTOM MADE OPTIONS:**

























# HS2SR10MF830DB


# HANCE G2 SEMIREC 1000 WW MFL DALI BK

## **PHOTOMETRIC DATA:**

HS2SR10MF830DB  $\eta$  = 100% Imax = 3354 cd/klm UTE: CIE: 101 100 100 100 100









# ACCESORIES:

# Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50



HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65C

## Description:

HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

# Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

# Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

HSSL50

# Description:

HANCE 1000/2000 ACC. SOFT LENS



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS