


HS2SR10MF840DB



HANCE G2 SEMIREC 1000 NW MFL DALI BK

Description:

LAMP semi-recessed multidirectional spotlight HANCE G2 SEMIREC 1000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25° middle flood reflector. LED COB, 4000K and CRI80. Electronic DALI control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 78.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Semi-Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.083 lm	⁰K :	4000
Plum:	8,6W	CRI :	80
Efficacy:	125,9 lm/w	R9 :	66
UGR:	<19	MacAdam:	3
Туре:	СОВ	Power Supply:	220-240V 50/60Hz
LED Lifetime:	78.000 L80B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	7W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:






HS2SR10MF840DB

HANCE G2 SEMIREC 1000 NW MFL DALI BK

PHOTOMETRIC DATA :



ACCESORIES :

Optical



Product code: HSCU50





Product code: HSHO50

Description: HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65C

Description: HANCE 1000/2000 ACC. RING DECO CO.



Product code: HSRI65M

Description: HANCE 1000/2000 ACC. RING DECO MET.



Product code: HSRI65W





Product code: HSSL50

Description: HANCE 1000/2000 ACC. SOFT LENS



Product code: HSTR50

Description: HANCE 1000/2000 ACC. DIF TRANS