


### HS2SR10MF940DW



### HANCE G2 SEMIREC 1000 9NW MFL DALI WH

## Description:

LAMP semi-recessed multidirectional spotlight HANCE G2 SEMIREC 1000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25º middle flood reflector. LED COB, 4000K and CRI90. Electronic DALI control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 78.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

Installation: Semi-Recessed

### **TECHNICAL SPECIFICATIONS:**

Light output: 924 lm °K: 4000 Plum: 8,6W CRI: 90 Efficacy: 107,4 lm/w R9: 66 UGR: <19 MacAdam: 3

Type: COB Power Supply: 220-240V 50/60Hz LED Lifetime: 78.000 L80B10 (Ta=25°C) Gear: Adjustable DALI

7W Power:

## Light output tolerance +/- 10%

























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU


















## **PHOTOMETRIC DATA:**


$$\label{eq:hammonic} \begin{split} &\text{HS2SR10MF940DW} \\ &\eta = 100\% \\ &\text{Imax} = 3354 \text{ cd/klm} \\ &\text{UTE:} \end{split}$$


CIE: 101 100 100 100 100




















Data according to regulations 2019/2020/EU and 2019/2015/EU



# ACCESORIES:

## Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50



HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65C

### Description:

HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

## Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

# Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

HSSL50

# Description:

HANCE 1000/2000 ACC. SOFT LENS



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS