


HS2SR10SP830NB



HANCE G2 SEMIREC 1000 WW SP BK

Description:

LAMP semi-recessed multidirectional spotlight HANCE G2 SEMIREC 1000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20º spot reflector. LED COB, 3000K y CRI80. Electronic ON OFF control gear included.IP20, IK07 ratings. Insulation Class II. LED life time: 78.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Semi-Recessed

TECHNICAL SPECIFICATIONS:

Light output: 995 lm °K: 3000 Plum: 8,6W CRI: 80 Efficacy: 115,7 lm/w R9: 60 UGR: <16 MacAdam: 3

Type: COB Power Supply: 220-240V 50/60Hz

LED Lifetime: 78.000 L80B10 (Ta=25°C) Gear: Electronic

Power:

Light output tolerance +/- 10%









































Data according to regulations 2019/2020/EU and 2019/2015/EU



















HS2SR10SP830NB


HANCE G2 SEMIREC 1000 WW SP BK

PHOTOMETRIC DATA:

HS2SR10SP830NB η = 100% Imax = 4956 cd/klm UTE: CIE: 102 100 100 100 100







Data according to regulations 2019/2020/EU and 2019/2015/EU



ACCESORIES:

Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50



HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65C

Description:

HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

HSSL50

Description:

HANCE 1000/2000 ACC. SOFT LENS



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS